





E-6110



Cosses cœur



type commercial standard

- Matière : acier doux
- Finition : zingage
- Certificat : 2.1

Dia câble	Largeur gorge	Longueur	Largeur	Longueur intérieure	Largeur intérieure	Poids par 100 pcs
mm	a mm	b mm	c mm	d mm	e mm	kg
3	3	24	18	15	10	0.4
4	4	25	19	16	11	0.5
5	5	31	22	22	16	0.6
6	6	37	29	26	19	1.5
7	7	44	32	32	22	2
8	8	51	38	34	24	2.6
9	9	57	42	38	29	6.5
10	10	64	44	42	32	4.8
11	11	70	51	48	35	7.5
12	12	76	57	51	38	8.5
14	14	82	60	57	40	10
16	16	89	64	60	42	12.6
18	18	102	69	67	45	22
20	20	115	79	76	51	26.8
22	22	127	89	83	54	33
24	24	140	102	88	64	39.5
26	26	152	105	102	68	66
28	28	165	115	110	73	77
30	30	178	121	115	79	99
32	32	203	133	140	93	119



G-6120



Cosses renforcées

- Matière : acier doux
- Finition : galvanisation
- Certificat : 2.1

Dia câble	Largeur gorge	Longueur	Longueur intérieure	Largeur intérieure	Épaisseur du dos	Poids par 100 pcs
mm	a mm	b mm	c mm	d mm	e mm	kg
8	8	51	35	22	4	5.2
10	10	64	47	30	4	9.8
12	12	76	57	35	5	14.8
14	14	89	65	45	6	19.2
16	16	102	76	50	6	25
18	18	114	86	53	8	38.6
20	20	127	94	60	9	55.6
22	22	140	107	65	10	93
24	24	152	114	70	10	85.2
28	28	178	130	80	10.5	150
32	32	203	157	100	10.5	161
36	36	229	177	115	12	363
40	40	254	198	120	12	376
44	44	279	214	130	15	608
50	50	305	215	140	20	960
56	56	356	245	160	20	1400
64	64	407	275	180	20	1700

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20