







Hand kettingtakels / Manual chain hoists

Eigenschappen

- » Fijn geslepen assen, nestenwiel met fijn geslepen passingen.
- » Remsysteem met stalen beveiligingsplaat.
- » Lagers in het nestenwiel voor geleiding.
- » Asbestvrije remschrijven.
- » Ratelschrijf met dubbel ratelpallen.
- » G80 gegalvaniseerde ketting.
- » Goed toegankelijk voor zelden voorkomende reparaties.
- » Beschikbaar in 3 series:
 - DELTA BLUE
 - DELTA BLACK
 - DELTA GREEN
- » Overlastbeveiliging beschikbaar voor DELTA BLUE series.
- » Met 3/6/10 m hijshoogte als standaard voorraad artikel, andere hijshoogtes op aanvraag.
- » Met lastketting getest volgens EN 818-7.

Features

- » Precision machined and highly finished shafts, sprocket and bearing housings.
- » Brake system with steel protected shield.
- » Roller bearing inside the chain sprocket is supporting the loadshaft.
- » Asbestos-free brake lining.
- » Ratchet disc with double ratchet pawls.
- » G80 galvanized chain.
- » Well accessible for seldom-or-never repairing.
- » Available in three series:
 - DELTA BLUE
 - DELTA BLACK
 - DELTA GREEN
- » Overload protection available for DELTA BLUE series.
- » With 3/6/10 m hoisting height as standard stock item, other hoisting heights upon request.
- » With load chain tested according to EN 818-7.



Bestelwijze / How to order

(081-060-082-061-064)

Takel model / Hoist type: DC 0 081 005 03

Hijshoogte / Hoisting height: 03

Productgroep / Productgroup: DC 0

Capaciteit / Capacity: 005

Specificaties / Specifications										
WLL / WLL (Ton)	0.25	0.5	1	1.5	2	3	5	10	20	
Test Load / Test load (kn)	3.2	7.5	15	22.5	30	45	62.5	125	250	
Inspanning voor max. lading / Effort for max. load	250	221	304	343	410	343	414	414	828	
Parten van hijsketting / Min. Chainfall	1	1	1	1	1	2	2	4	8	
Diameter Hijsketting / Chain Diameter (mm)	4	6	6	8	8	8	10	10	10	
Netto Gewicht / Net Weight (kg)	1,8	8,5	11	18	18	27	42	83	193	
Measurement / Afmetingen	23x8x10.5	25.5 x 18.5 x 13,7	25,5 x 20,5 x 14,7	33 x 25,5 x 16.2	33x25.5x16.2	36 x 27 x 16.2	43 x 34 x 19.2	50 x 41 x 21	64 x 38 x 64	
Extra gewicht hijshoogte / Extra weight extra lift	0.41	1.7	1.7	2.3	2.3	3.7	5.6	9.7	19.4	
Afmetingen / Dimensions (mm)										
	0.25	0.5	1	1.5	2	3	5	10	20	
A	92	113	126	141	141	141	163	163	191	
B	72	125	147	183	183	183	215	404,5	595	
C	85	255	306	368	368	486	616	750	1000	
D	30	36	40	45	50	58	64	85	110	
K	25	30	34	38	41	48	52	64	85	